



Intelligence for business.



Features

- True-flat, bezel-free design
- Durable and sturdy base
- Supports integrated MSR and 2nd display
- Proven reliable performance
- Built-in universal power supply
- Built-in speakers
- USB touch interface

LE1015

15" LCD Touch Monitor

The Bematech LE1015 true-flat, bezel-free touch monitor is designed and manufactured to meet the requirements of retail and restaurant operations with their Point-of-Sale system. The highly rugged touch monitor includes a solid base with extra wide hinge for maximum stability. The LE1015 also facilitates quick and professional mounting of integrated magnetic stripe reader and VFD/LCD customer display.



bematechus.com

LE1015 SPECIFICATIONS

LCD TOUCH PANEL

LCD size	15"
Display active area	11.97" x 8.98" (304.1 x 228.1mm)
Brightness	250 cd/m ²
Response time	12ms
Contrast ratio	800:1
Resolution	XGA 1024 x 768 @ 75Hz, 16.2M colors
Viewing angle (CR≥10)	Horizontal: 160°, Vertical: 145°
Touch screen	5-wire resistive touch panel, USB interface

MECHANICAL

Net weight	12lbs (5.5Kg)
Dimension (W x D x H)	14.33" x 9.06" x 12.83" (364 x 230 x 326mm)
Color	Black

ELECTRICAL

Power supply	Built-in universal power Input 100~240VAC, 50/60Hz
Power consumption	30W max Power saving mode 1W max Power off mode 0.5W max

ENVIRONMENTAL

Operating temperature	41°F - 104°F (5°C - 40°C)
Relative humidity	20% - 80%, non-condensing

MISCELLANEOUS

Plug & Play	DDC2B
VESA wall mount compatible	3.94" x 3.94" (100 x 100mm)
Power management	VESA DPMS
Magnetic stripe reader (optional)	Track 1/2/3, USB interface
Customer display (optional)	8" LCD or 2x20 VFD, USB interface



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

