

Stratos 2400 Series

Bioptic Scanner/Scale

Honeywell's Stratos® 2400 5-sided, 360°-bioptic scanner/scale increases productivity in demanding, high-volume seated environments where shorter vertical towers are required, and poor quality and high-density bar codes are prevalent. Independent scanning planes and a modular design lower maintenance costs and ensure continuous operation.

The Stratos 2400 series provides retailers with the ability to deploy a single scanner platform across multiple store formats around the world, including stores with 353 mm (13.9"), 399 mm (15.7"), and 508 mm (20") scanner footprints.

Aggressive scan performance on high density and poor quality bar codes minimizes the need for manual keying. The 2400 also excels at scanning GS1 DataBar™ codes, ensuring compliance with sunrise initiatives.

Rapid pass-through scanning allows cashiers to maintain a constant motion across a wide range of bar codes, leading to faster customer processing, shorter lines, optimization of the number of open checkout lanes, and lower labor and energy costs.

Unlike other bioptic devices, 2400 is the only one to offer pre-aligned optical scanning modules, and independent scanning planes which enable the scanner to maximize uptime and maintain productivity.

The Stratos 2400 maximizes return on investment with two analytical tools for tracking, managing and improving checkout productivity and efficiency. StratosSTATS™ provides real-time visibility into key data points directly impacting checkout productivity. StratosSCHOOL™ captures information necessary to improve operator scanning techniques and safety.



Features

- **5-sided, 360°-Scanning:** Improves productivity and operator ergonomics by reducing product orientation
- **StratosSYNC™ Independent Scanning Planes:** Maintains productivity and uptime via independent scanning planes
- **StratosSCHOOL Operator Training Software:** Improves productivity and promotes safer scanning techniques
- **StratosSWAP™ Pre-Aligned Optical Scanning Modules:** Minimizes downtime and lowers the cost of service via modular optical scan engines
- **StratosSTATS Productivity Analytical Software:** Provides data critical to maintaining checkout productivity
- **Remote MasterMind™ Scanner Management Software:** Offers a quick and convenient solution for IT administrators seeking to manage all scanners within their network from a single remote location
- **Flip-Up Weigh Bar:** Single or three-sided options allow cashiers to accurately weigh oversized produce, reducing shrink loss

Stratos 2400 Technical Specifications

Operational

| | |
|------------------------|---|
| Light Source | Visible Laser Diode 650 nm ± 10 nm |
| Visual Indicators | Steady Blue = ready to scan; Flashing Blue = good read; Amber = scale at zero; 7-segment display = diagnostic indicator |
| Host System Interfaces | USB, RS232, IBM46xx (RS485) |
| Auxiliary Ports | RS232: Secondary scanner, EAS |

Mechanical

| Product | Length | Width | Depth (Below Counter) | Height (Above Counter) |
|-------------------------------------|----------------|----------------|-----------------------|------------------------|
| 2420 (compact scanner with scale) | 399 mm (15.7") | 292 mm (11.5") | 100 mm (4") | 130 mm (5.1") |
| 2421 (compact scanner only) | 399 mm (15.7") | 292 mm (11.5") | 100 mm (4") | 130 mm (5.1") |
| 2422 (sub compact scanner only) | 353 mm (13.9") | 292 mm (11.5") | 100 mm (4") | 130 mm (5.1") |
| 2430 (full-size scanner with scale) | 508 mm (20") | 292 mm (11.5") | 100 mm (4") | 130 mm (5.1") |
| 2431 (full-size scanner only) | 508 mm (20") | 292 mm (11.5") | 100 mm (4") | 130 mm (5.1") |

Electrical

| | |
|-----------------|---------------------------------------|
| Input Voltage | 5.2 VDC ± 0.25 VDC; 12 VDC ± 0.5 VDC |
| Operating Power | 11 W (1670 mA @ 5.2 V; 190 mA @ 12 V) |
| Standby Power | 5.5 W (610 mA @ 5.2 V; 190 mA @ 12 V) |

Environmental

| | |
|-----------------------|--|
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -40°C to 60°C (-40°F to 140°F) |
| Humidity | 5% to 95% relative humidity, non-condensing |
| Environmental Sealing | Sealed to resist airborne particulate contaminants |
| Light Levels | 4842 Lux |

Scan Performance

| | |
|----------------------------------|---|
| Depth of Scan Field (Horiz/Vert) | H: 0 mm - 100 mm (0"-4"); V: 0 mm - 216 mm (0"-8.5") for 0.33 mm (13 mil) bar code |
| Sides Read/Scan Zone | 5 / 360° |
| Scan Pattern | Omnidirectional: 54 scan lines (Horizontal: 38 scan lines; Vertical: 16 scan lines) |
| Scan Speed | 5400 scan lines per second |
| Resolution | 4.5 mil (0.114 mm) |
| Print Contrast | 35% minimum reflectance difference |
| Decode Capability | Reads standard 1D and GS1 DataBar symbologies |
| Warranty | 2 year factory warranty |

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance
 For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies



For more information:
www.honeywellaidc.com

| Scale Specifications | |
|-----------------------|--|
| Capacity | 15 kg (30 lb) |
| Minimum Legal Weight | 0.005 kg (0.01 lb) |
| Maximum Static Weight | 68 kg (150 lb) |
| Adjustments Required | Field calibration if necessary |
| Applications | Weight-only and price computing |
| Scale Partners | Avery Berkel®, Bizerba®, Dibal®, Digi®, Herbert Retail and Mettler Toledo® |
| Platter Options | Single or three-sided flip-up bar for weighing oversized produce |

Honeywell Scanning & Mobility

9680 Old Bailes Road
 Fort Mill, SC 29707
 800.582.4263
www.honeywell.com





www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

