

Voyager 9520/VoyagerCG 9540

Single-Line Laser Scanners

Honeywell's Voyager® 9500 series of hand-held, single-line laser scanners offer aggressive scanning of all standard 1D bar codes.

The Voyager series of hand-held, single-line bar code scanners have united form with function in becoming the industry benchmark for value and performance.

These sleek scanners feature patented automatic infrared activation and decode all standard 1D bar codes, including GS1 DataBar™ (formerly known as RSS codes).

VoyagerCG 9540 also includes patented CodeGate® technology which allows the user to easily target the desired bar code and complete data transmission with the press of a single button.

For presentation scanning, Honeywell offers a stand with automatic in-stand detection technology.



Features

- **Automatic Trigger:** Use scanner as either a hand-held device or a fixed presentation scanner when mounted in the stand
- **650-nanometer Laser:** High-visibility laser allows user to place laser line on selected bar code
- **CodeGate Technology (VoyagerCG 9540 only):** Zero in on desired code and complete data transmission with the push of a single button—ideal for menu scanning applications
- **Flash ROM:** Future proof POS system with free firmware updates via MetroSet®2 software and standard PC
- **Parsing (Data Editing):** Format bar code data to meet host system's specific requirements

Voyager 9520/VoyagerCG 9540 Technical Specifications

Mechanical

| | |
|--------------------|---|
| Dimensions (LxWxH) | 198 mm x 78 mm x 56 mm (7.8" x 3.1" x 2.2") |
| Weight | 149 g (5.3 oz) |

Electrical

| | |
|------------------------|---|
| Input Voltage | 5 VDC \pm 0.25 V |
| Operating Power | 825 mW (165 mA @ 5 V) |
| Standby Power | 600 mW (120 mA @ 5 V) |
| Host System Interfaces | USB, RS232, Keyboard Wedge, IBM 46xx (RS485), OCIA, Laser Emulation, Light Pen Wand Emulation |

Environmental

| | |
|-----------------------|--|
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -40°C to 60°C (-40°F to 140°F) |
| Humidity | 5% to 95% relative humidity, non-condensing |
| Drop | Designed to withstand 1.5 m (5') drops |
| Environmental Sealing | Sealed to resist airborne particulate contaminants |
| Light Levels | 4842 Lux |

Scan Performance

| | |
|---------------------|---|
| Scan Pattern | Single scan line |
| Scan Speed | 72 scan lines per second |
| Scan Angle | Horizontal: 50° |
| Print Contrast | 35% minimum reflectance difference |
| Pitch, Skew | 68°, 52° |
| Decode Capabilities | Reads standard 1D and GS1 DataBar symbologies |
| Warranty | 5 year factory warranty |

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance
 For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies



For more information:
www.honeywellaidc.com

| Voyager 9520/VoyagerCG 9540 Typical Performance* | |
|---|-------------------------------|
| Narrow Width | Depth of Field |
| 5.2 mil | 13 mm - 51 mm (0.5" - 2.0") |
| 7.5 mil | 0 mm - 127 mm (0" - 5.0") |
| 10.4 mil | 0 mm - 165 mm (0" - 6.5") |
| 13 mil | 0 mm - 203 mm (0" - 8.0") |
| 21 mil | 25 mm - 254 mm (1.0" - 10.0") |
| *Resolution: 5 mil (0.127 mm) | |
| *Performance may be impacted by bar code quality and environmental conditions | |

Honeywell Scanning & Mobility

9680 Old Baires Road
 Fort Mill, SC 29707
 800.582.4263
www.honeywell.com





www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

