

# Near-Edge Performance Printer



## Intelligent Industrial Thermal Printer ■ ■ ■

### features at a glance ■ ■ ■

- **Near Edge Printhead** - allows full use of the label giving customers the ability to design and code barcodes that support detailed information. The flexible multimedia printing allows labels to be printed on synthetics, tags, self-adhesives and plastics.
- **PCL5e & PCL6 Standard Language** - makes graphics integration easier and allows users to spend less time setting up printers. Offers virtually endless application choices.
- **Easy ERP integration** - a benefit that derives from true PCL5e & PCL6 thermal barcode printers. Middleware applications are no longer necessary within printer networks. All Performance printers are approved through the SAP® Printer Vendor Program.
- **Laser and inkjet printer** - users can realize the benefits of a ruggedized thermal barcode printer and reduce operating costs with seamless integration of true PCL5e & PCL6 devices.
- **Media auto-loading and calibration** - to give printer operators freedom from complex and time consuming media setup.
- **Graphic color touchscreen** - display with an intuitive menu flow making the user interface and navigation seamless.
- **Die cast frame** - and metal covers designed specifically for harsh work environments.
- **Standard 300 dpi printhead** - with each Performance Series printer allows users to now benefit from a higher resolution printhead with better text, images and barcodes at a 203 dpi printhead price.
- **50 resident scalable fonts** - is the new standard in thermal barcode printing. No longer restricted to a limited font selection, users can create custom labels on-demand.

The Datamax-O'Neil p1120n Near Edge Performance Printer offers a unique near-edge printhead that allows full use of the label giving customers the ability to design and code barcodes that support detailed information. The flexible multimedia printing allows labels to be printed on synthetics, tags, self-adhesives and plastics. The near-edge printhead gives users the ability to integrate barcode printing across a wide variety of applications. The p1120n also offers auto-loading capabilities, a user-friendly touchscreen, and uses industry standard PCL printer language making it easy to integrate.

Like the rest of the Performance Series printers, the p1120n was designed to resolve a number of issues customers have been having with thermal printers for many years. This had resulted in a printer family that is the easiest to load, easiest to use and easiest to integrate of any thermal printers available anywhere. The inclusion of Incorporating PCL, an industry standard printer language, allows the printer to run on a variety of operating systems, so it is independent of any application software running on a computer. This ensures faster and easier plug-play integration, getting your printer systems up and running sooner.

### popular applications ■ ■ ■



#### Manufacturing

- Asset Tracking
- Finished Goods Marking
- Agency Labels
- Case Labels



#### Transportation and Logistics

- Cross Docking
- Sorting Centers
- Shipping Labels
- Pallet Tracking



#### Horticulture

- Plant Stakes up to .025"/.635mm Thick
- Tree Wraps
- Polyester Pot Labels



#### Pharmaceuticals

- Compliance Labels
- Product Identification
- Track and Trace
- Pick Lists

### your benefits ■ ■ ■

**Non-Proprietary PCL** – The Performance Series offers PCL, a globally adopted standard/laser compatible printer language that allows easy integration into SAP® and other network environments.

**Most Advanced Interface** – The industry's most intuitive color touchscreen makes set up and performance enhancements as simple as 1-2-3. The printer provides front panel print quality adjustments, auto media calibration and loading as well as ribbon tensioning controls.

**Options Galore!** – The Performance Series printers are available with numerous options to meet the most diverse requirements. Some of the options include internal rewinder, peeler and cutter, USB host, GP 1/0, 802.11 b/g, audio alarm.

**Lower Cost of Ownership** – Lower your total cost of ownership with Zero label waste auto loading design. Other printers waste labels every time you load the printer. Stop wasting labels.

#### Easiest Setup and Network Management.

- Use your Standard Network Management tools!
- Like Tivoli and HP OpenView
- Network Time Protocol (NTP)
- Robust SNMP support.
- HTTP Web Server
- FMAudit Global MPS Solution Ready Printer
- Works with Print Audit a leading MPS solution



datamax • o'neil  
by Honeywell

# product specifications ■ ■ ■

## physical characteristics ■ ■ ■

- Printhead Technology
  - » 300 dpi Near Edge
  - » Max Print Width 4.27" (108.5mm)
  - » Max Print Speed 8ips (203mmps)
  - » Max Feed speed 8ips (203mmps)
  - » Max Back up speed 5ips (127mmps)
  - » Patent Pending Automatic Printhead pressure adjustment. (increases printhead life)
  - » Printhead cooling fan
- Dimension
  - » WxDxHin | 10.8x 18.7x11.9, WxDxHmm | 274x 475x302
- Weight
  - » 41lbs. / 19kg
- Operating temperature
  - » Operating: 32°F (0°C) to 104°F (40°C)
  - » Storage: -4°F (-20°C) to 140°F (60°C)
- Power source
  - » Universal (PFC-compliant) power supply 90-264 VAC; 47-63Hz
- Construction
  - » Solid Aluminum Die Cast Powder coated Frame, with metal side opening cover to load media with a large clear media window
- Safety
  - » Media Cover open warning
- Control Panel
  - » Graphic 320 x 240 Color touch Screen Display with wallpaper.
- Memory
  - » 32MB Flash/64MB SDRAM
- Real Time Clock
  - » Real Time Clock (RTC) with user replaceable 3 year battery
  - » Paper Low Sensor and Ribbon Low Sensor
  - » Capable of paper low notification, reducing down time.
- Printer Type
  - » Direct Thermal (Optional Thermal Transfer)

## integration ■ ■ ■

- Communication Interfaces
  - » USB 2.0 Device Standard
  - » 10/100 Base-T Ethernet Standard
  - » Wireless Module- 802.11 b/g Optional
  - » Applicator GP I/O & Serial (RS-232C) Port Optional
  - » USB Host connection Optional
- Security Protocols:
  - » WEP WPA WPA2
  - » Modes PSK/Enterprise
  - » Security/Encryption 64/128 TKIP/RC4 CCMP/AES
  - » Authentication LEAP, EAP-PEAP, EAP-FAST, EAP-TTLS, EAP-LEAP, IPV4
- Network/Software support:
  - » DHCP, TCP/IP, UDP, DNS, BOOTP, NTP, SSH
  - » SNMP, Robust MIB
  - » Embedded Configurator: Resident printer configuration tool
  - » Embedded Network web pages
  - » Drivers: Windows® XP, Windows® 7, Windows® 8 & 8.1
  - » Network Management is done with your standard HP Compatible network management tools. Works with HP Openview®, Tivoli® and others.
  - » Network Time Protocol Rev 4 for Computer Security Log Management SP800-92
  - » Encryption Protocol: **Wired and wireless connections**
    - » AES 256 for secure data transmission for healthcare, pharmaceutical, USA government and retail applications. Meet HIPPA and FIPS 170.210 and 140-02 encryptions requirements

- Apple
  - » Works in MacBook Pro® with the HP Laserjet® Series PCL4/5 driver
- Linux and Unix
  - » Cups Drivers
- SAP®
  - » SAP® ready. (device type YDM1120)
- DocOrigin Certified

## accessories ■ ■ ■

External rewriter  
Media Catch tray

## barcodes/fonts/graphics ■ ■ ■

- Bar Codes
  - » Aztec, Codabar, Code 128 Autoswitch, Code 128 Code Set A, Code 128 Code Set B, Code 128 Code Set C, Code 3 of 9, Code 93, DataMatrix, EAN-13, EAN-8, Extended Code 3 of 9, FIM, GS1 Databar (RSS), GS1-128(UCC/EAN Code 128), HIBC, Interleaved 2 of 5 with a module 10 checksum, & shipping bearer bars, MicroPDF417, PDF-417, Planet, Plessey, Postnet, QR Code – Auto format, Telepen, UPC-A, UPC-E, UPS MaxiCode
- Fonts
  - » 50 Standard resident Scalable fonts: Albertus Medium, Albertus Extra Bold, Antique Olive, Antique Olive Italic, Antique Olive Bold, Arial, Arial Italic, Arial Bold, Arial Bold Italic, Clarendon Condensed Bold, Coronet, Courier, Courier Italic, Courier Bold, Courier Bold Italic, Garamond Antiqua, Garamond Kursiv, Garamond Halbfett, Garamond Kursiv Halbfett, Letter Gothic, Letter Gothic Italic, Letter Gothic Bold, Marigold, CG Omega, CG Omega Italic, CG Omega Bold, CG Omega Bold Italic, CG Times, CG Times Italic, CG Times Bold, CG Times Bold Italic, CG Triumvirate Bold, CG Triumvirate Bold Condensed, Times New Roman, Times New Roman Italic, Times New Roman Bold, Times New Roman Bold Italic, Univers Medium, Univers Medium Italic, Univers Bold, Univers Bold Italic, Univers Condensed Medium, Univers Condensed Medium Italic, Univers Condensed Bold, Univers Condensed Bold Italic, Symbol, Wingdings, OCR-B, OCR-A
- Downloadable Font Types
  - » True-Type, PCL Bitmap (300 dpi)
- PCL Macros
  - » Multiple PCL Macros can be store in flash.
  - » Overlay Macros can be used and store in flash.
- Graphics
  - » Full support of PCL5e & PCL6 and GL/2 graphics capability is provided. (Support of various host based file formats such as PCX, BMP are not part of the PCL5e & PCL6 standard but are supported and converted by standard applications) Industry standard printer language HP P JL, HP PCL 5e, HP GL/2 and HP XL, printer languages with auto

language select in addition to extensions for barcode. Also provides standard bi-directional communications capabilities.

## warranty ■ ■ ■

- Printer\*: 1 year (including platen roller and installed options)
  - Printhead\*: 1 year or 1,000,000 inches whichever comes first
  - Contact sales representative for extended warranty options
- \*when used with approved supplies

## media supply ■ ■ ■

- » Roll-fed, die-cut, continuous labels: perforated or continuous tag/ticket stock 8-inch/203mm roll max diameter on 3-inch/76mm core). Fan fold stock accepted.
- Media thickness range:
  - » 0.0025" - 0.025" (0.0635mm - 0.635mm)
- Top-Of-Form Sensor/Media Sensing Double Sided, adjustable position for label gap, notch and reflective black mark on bottom or top of form.
- Label backfeed:
  - » For use with optional cutter & Peel and Present.
- Ribbon
  - » Near edge ribbons
  - » Core: 1.0" (25.4mm)
  - » Length: 1968' (600m)
  - » Coated side in and coated side out
- Reference model above for width.

## options ■ ■ ■

- Thermal Transfer
- Internal Powered Rewind with adjustable tension.
- Peel & Present
- Cutter
- Cutter Tray
- Audio Alarm
- 1" or 1.5" Media Hub Adapters
- Expanded 64MB Flash Memory

## agency approval ■ ■ ■

CE, UL, C/UL, UL Mexico CoC and other approvals.  
Contact sales representative for the most current approval list.



datamax • o'neil  
by Honeywell

[www.datamax-oneil.com](http://www.datamax-oneil.com)



Datamax-O'Neil is a silver-level member of the SAP® Printer Vendor program. The Datamax-O'Neil Performance Series printers are compliant with all requirements for device types as defined in the SAP® Printer Vendor program.

Specifications subject to change without notice.  
Copyright 2015, Datamax-O'Neil (rev3.3.15)



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

Get in touch with us  
on social media!

