

PB₂/PB₃

Commercial Mobile Receipt Printers



- Compact and lightweight for all-day use
- Compatible with popular Intermec CN Series and CK3 mobile computers
- Long life, field replaceable batteries
- Choice of Bluetooth®, WLAN, or IrDA communications, plus standard Serial
- On-board memory supports resident fonts, logos, graphics
- Optional magnetic stripe reader
- Optional environmental case for adverse conditions

Comfortable enough to wear all day, the lightweight and compact Intermec PB2/PB3 two- and three-inch commercial receipt printers meet the needs of the mobile workforce in DSD/route accounting, retail queue busting and field service applications. Long-lasting, field replaceable batteries and weather-resistant construction ensure the PB2/PB3 delivers dependable, all-day service, whenever and wherever required.

The ideal companion to Intermec worldclass mobile computers and scanners, the PB2/PB3 printer interfaces seamlessly via Bluetooth® or 802.11g with the CN and 700 Series handheld computers, as well as with the Intermec CK3. The PB2/PB3 also has the ability to print from a wide range of handheld devices and smart phones to produce receipts on demand. Available with optional card reader, the PB2/PB3 gives workers the flexibility to accept payments via their mobile computer or their printer. Either way, the combination supports increased productivity and customer satisfaction, enabling workers to process payments on the go and generate receipts immediately.

The PB2/PB3 and its accessories are designed for easy mobility. The most compact and lightweight of Intermec's

mobile printers, the PB2/PB3 can be comfortably worn all day, using the included belt loop or optional shoulder strap for convenient, hands-free operation. For added protection in outdoor applications such as issuing electronic citations and processing car rental returns, the PB2/PB3 offers an optional IP54-rated environmental case that provides extra weather resistance without affecting mobility.

With multiple connectivity options and robust, field-replaceable batteries, the PB2/PB3 is always ready to work. Batteries can be charged independently of the printer unit, maximizing uptime and convenience. And the PB2/PB3 comes with secure Bluetooth, 802.11 or IrDA wireless connectivity, as well as standard serial communication.

Priced affordably to enable efficient, cost-effective receipt printing where and when it's needed, the PB2/PB3 commercial receipt printers help companies increase the return on their mobility investment. The PB2/PB3 printers are part of a complete hardware solution from Intermec, that also includes Intermec receipt media and Medallion Support services, as well as a full range of AIDC products.

Physical Characteristics

	PB2	PB3
Width	103.23 mm (4.06 in)	127.20 mm (5.01 in)
Height	60.96 mm (2.40 in)	57.69 mm (2.27 in)
Length	138.58 mm (5.46 in)	156.10 mm (6.14 in)
Weight – printer only		
	314 g (11.1 oz)	422 g (14.9 oz)
Weight – with battery & media roll		
	472 g (16.7 oz)	583 g (20.6 oz)

Environmental

Operating temperature: -10°C to 50°C (14°F to 122°F)

Storage temperature: -20°C to 60°C

(-4°F to 140°F) without battery

Operating humidity: 20% to 85% non-condensing

Storage humidity: 5% to 95% non-condensing

Rain & Dust Resistance: IP54 with

optional environmental case

Drop spec: Survives 1.5m (5 ft.) drop to concrete

Power

Battery: Rechargeable 7.4V Li-Ion, 2200mAh.

Battery rechargeable up to 8.5V.

Recharging: approximately 180 minutes

Charging temperature: 10°C to 25°C (68°F to 77°F)

Battery storage temperature: 4°C to 40°C

(40°F to 104°F)

Endurance per fully charged battery at 25% print

density: PB2: 256 m (842 ft); PB3: 194 m (636 ft)

AC Adapter: 100 to 240 VAC @0.4A; meets CEC EPS

Memory

RAM: 1MB

Flash: 4MB

Standard Communications

RS-232 Serial

Optional Communications

Bluetooth® (v2.0, Class II)

IrDA

802.11g

Wireless Security

Authentication and Encryption Options:

WPA-PSK/WPA2-PSK; LEAP; WEP 64/

WEP 128; TKIP and AES/CCMP

Optional Card Reader

Magnetic Stripe Reader (MSR) 3 track -

ANSI/ISO 7810, 7811 standards

Print Speed and Resolution

203 dpi (8 dots/mm)

PB2: up to 2+ ips (56mm/s at 7.2V;

25C and 64 dots fired) at 8.5V

PB3: up to 2 ips (50mm/s at 7.2V;

25C and 64 dots fired) at 8.5V

Print Technology

Printhead: Direct thermal

Maximum print width:

PB2: 48mm (1.89 in); **PB3:** 72mm (2.83 in)

Media

Type: Receipt media

Width: PB2: 57mm (2.25 in); PB3: 79mm (3.125 in)

Media length: Continuous

Thickness: up to 4 mil

Core ID: 10mm (0.4 in)

Capacity: PB2: 18m (60 ft); PB3: 13m (44 ft)

Software

Programming Language

ESC-P command sets (Line Print and Easy Print modes)

Character Sets

Standard: English and Latin

Optional: Arabic, Simplified Chinese, Traditional Chinese, Cyrillic, Greek, Hebrew, and Polish

Resident font sizes: PB2: 24, 32, 38, 40, 48 characters

per line; PB3: 36, 48, 57, 63, 72 characters per line

Additional character sets can be printed

using software from FieldSoftware.com

Graphics

Supports user-defined fonts, graphics, formats

and layouts, including custom logos

Barcode Symbolologies

1D: Codabar, Code 39, Code 128 Subset A-C, UCC/

EAN-128, Interleaved 2 of 5, UPC/EAN/JAN

2D: PDF417

User Interface

Three Multi-function Status LEDs: Power on,

Bluetooth® or 802.11g radio on, low battery,

battery charging, card reader ready (for

MSR options), print error, paper out.

Ships with

Printer, battery, universal AC adapter,

belt loop, one roll of media, printhead

cleaning pen, quick start users guide

Accessories

Universal AC charger with four socket adapter

plugs, belt loop, shoulder strap, IP54 protective

environmental case, card reader cleaning cards,

printhead cleaning pen, battery, two-bay battery

charger, cigarette lighter adapter/12V vehicle

battery charger, serial cable, developers kit.

Warranty

One year; additional Medallion

service packages available

North America

Corporate Headquarters

6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

North Latin America Headquarters Office

Mexico
Phone: +52 55 52-41-48-00
Fax: +52 55 52-11-81-21

South Latin America

Headquarters Office

Brazil
Phone: +55 11 5502.6770
Fax: +55 11 5502.6780

Europe/Middle East & Africa Headquarters Office

Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific

Headquarters Office

Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW:
00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799



Copyright © 2009 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611906-01F 07/09

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

