



TB3 Trio Thermal Printer



Features

- Direct Thermal
- Drop in Paper Loading
- High Speed Printing (200mm/s)
- Bar Code Printing
- Epson Compatible

3-in-1 Interface Includes:

- Serial
- Ethernet
- USB

The TB3 Trio is Touch Dynamic's latest version of the reliable TB3 Printer Series. The TB3 Trio features three interface's on each printer including Serial, USB and Ethernet. The triple interface enables customers to stock one product and meet all their roll out needs. The TB3 Trio boasts Jam Free Auto Cutter technology to deliver an extremely reliable printer solution.



TB3 Trio Thermal Printer

TOUCH
DYNAMIC

TB3 Trio Specifications		
Print method		Direct Thermal
Print speed		200mm/sec
Print buffer		4K (can be increased to 12K on special order)
Resolution		180dpi x 180dpi
Dot pitch		0.141mm x 0.141mm
Effective printing width		72mm, 512 dots/line
Printing direction		Unidirectional with friction feed
Character per line		Font A (12x24) 42 columns Font B (9x17) 58 columns
Paper	Type	Thermal paper
	Width	50mm ~ 82.5mm (2in ~ 3.5in)
	Thickness	0.06 ~ 0.09mm
	Roll diameter	Max 80mm (3.5in)
Reliability	Tph life	160Km
	Mcbf	60,000,000 lines
Character set	Alphanumeric character	95
	Extended graphic	128x18 page
	International character	14
Barcode		EAN-8, EAN-13, CODE39, ITF, UPC-A, CODEBAR, CODE 93, CODE 128, PDF417(20)
Emulation		ESC/POS COMMAND COMPATI-BLE
Drawer port		1 port
Interfaces included		Serial, USA, Ethernet
Power	Type	External SMPS
	AC	100-240V 50/60Hz
	DC	24Vdc / 1.75A
Dimension	WxDxH	6.3x8.5x6.25 in
Weight	Includes auto cutter	3.75lbs





www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

