

Product profile

SF61B

Pocket Scanner for
Healthcare Applications



ERGONOMIC

Compact enough to move with the clinician, the SF61B can be quickly stowed in a smock pocket when use of both hands is needed



RADIO

Bluetooth® wireless pairs easily with iOS®, Android® and Windows Mobile® devices, with a range of up to 100 m (325 ft)



SCANNING

Includes the industry's fastest 2D imaging technology for highly responsive, omni-directional scanning even on curved or translucent surfaces



HEALTHCARE

Disinfectant-ready housing with IP64 seal rating protects against the harmful effects of repeated chemical wipe-downs



LASER-FREE

Completely safe laser-free design with LED aimer is ideal for patient-facing applications



BATTERY

Field-replaceable battery provides greater than full-shift battery life, even in scan-intensive applications

Automated data capture is fundamental to ensuring patient safety in healthcare workflows, driving an increased demand for barcode scanners that can move *with the clinician*. To address this challenge and make it easier to collect data at the point of care, we developed the SF61B healthcare pocket scanner. Small enough to stow in a pocket, it travels with the clinician and can be quickly accessed or securely tucked away when use of both hands is required. This makes it ideal for today's busy healthcare environment, where complete freedom of movement is essential and the ability to scan should always be within arm's reach.

The SF61B integrates with existing healthcare information management systems and—with the simple scan of a barcode—easily pairs with iOS, Android and Windows Mobile smartphones and tablets. Its compact form factor is small enough to fit into awkward or constricted spaces, and a high performance imager makes it easy to scan all 1D and 2D codes—regardless of angle or orientation.

To ensure safe operation in patient-facing applications, the SF61B uses a laser-free design that provides high performance scanning without the risk of eye injury inherent in laser-based designs. Its powerful white illumination field can even double as a makeshift flashlight.

As a pocket scanner, the SF61B was engineered for all-day wireless performance. An integrated Bluetooth Class 1 radio enables wireless communication at ranges up to 100 m (325 ft) from the host, and its field-replaceable battery has been tested to last up to 25,000 scans on a single charge.

The SF61B is also highly customizable to complement your healthcare environment. With our free EasySet™ PC programming tool, you can adjust security settings, beeper volume, and even enable vibration feedback. For example, a simple scan of a bar code can enable silent scanning for quiet areas, and audible tones can be easily re-enabled for noisy environments. EasySet can also be used to generate printable configuration bar codes, making it easy to setup additional scanners to match.

Physical Characteristics

Dimensions (LxWxH), including ring end-cap:
16.0 cm (6.3 in) x 4.6 cm (1.8 in) x 3.9 cm (1.5 in)
Weight: 184 gm (6.5 oz)

Electrical Specifications

Battery: Lithium-ion rechargeable (2,600 mAh)
Battery Life¹: 28,000 scans (1D) or 25,000 scans (2D), with 1 scan every 4 seconds²
Recharging Time: 3 hours

¹ Battery life may vary depending on ambient temperature, ambient light and battery life.
² Typical number of scans possible without a battery recharge, in a typical office environment (250 lux) at ambient temperature.

Bluetooth Radio

Type: Bluetooth Class 1 v2.1+EDR
Frequency: 2.4 GHz with Adaptive Frequency Hopping
Range: 100 m (325 ft) in open space, 30 m (100 ft) in typical work environment
Profiles: HID, SPP

Connectivity

Operating System Compatibility: Apple iOS[®]; Google Android[®]; Microsoft Windows[®] XP, Vista, 7, 8

Scan Technology

Intermec 2D Imager with LED Aimer (EA31)

Reading Performance

Maximum Code Resolution:

1D: 4 mils

2D: 6.6 mils

Print Contrast:

1D: 20%

2D: 20%

Motion Tolerance: Up to 120 in/s

User Feedback

- Indicator LED
- Configurable buzzer
- Configurable vibrator (haptic feedback)

1D Bar Code Symbolologies Supported

Codabar, Code 11, Code 39, Code 93/93i, Code 128 / GS1-128, EAN/UPC, GS1 DataBar Limited, GS1 Composite (linear only), GS1 DataBar Expanded, GS1 DataBar Limited, GS1 DataBar Omnidirectional, GS1 DataBar Stacked, Interleaved 2 of 5, Matrix 2 of 5, MSI, Plessey, Standard 2 of 5, Telepen

2D Bar Code Symbolologies Supported

DataMatrix, QR Code, Micro QR, PDF417, Micro PDF417, Aztec, Maxicode, Han Xin, Codablock A, Codablock F, GS1 Composite, TLC 39

Postal Bar Code Symbolologies Supported

Australian Post, BPO, Canada Post, Dutch Post, Infomail, Intelligent Mail, Japan Post, Planet, Postnet, Sweden Post

Environment

Housing: Disinfectant ready
Operating Temperature: -20°C to +50°C (-4°F to +122°F)
Storage Temperature: -40°C to +70°C (-40°F to +158°F)
Charging Temperature: 0°C to 45°C (32°F to 113°F)
Relative Humidity: 5 to 95% non-condensing
Drop: 26 drops from 2m (6.5 ft.) to concrete
Environmental Rating: IP64
Ambient Light: 0 to 100,000 lux

Regulatory Approvals & Compliance

1016SP01B (SF61B)
Safety: cULus Listed, CDRH, CE
EMC: Class B - FCC/ICES, CE
Radio: FCC, IC, CE, IDA (Singapore), IFETEL (Mexico), A-Tick
Other: BIS, ANATEL, EAC, NTC, SIRIM, MSIP, EU Directives-WEEE, RoHS, Batteries & Accumulators, Packaging & Waste Packaging

Standard Warranty

Three year standard warranty, with extended protection available through Intermec Medallion Support Services.

Accessories

View the SF61B Accessory Guide for complete details.

- Belt Clip Holder*
- Charger, Single-Bay*
- Charger, Quad-Bay*
- FlexDock Cup, Dual-Charge
- FlexDock Cup, Quad-Charge
- Power Adapter, AC
- Power Adapter, USB
- Wireless Base Station*

* These accessories, originally developed for SF51, are also compatible with SF61B.

Typical Reading Distances³

Symbology	Density	Minimum Distance	Maximum Distance
Code 39	0.1 mm (4 mils)	4 cm (1.6 in)	18 cm (7.1 in)
	0.125 mm (5 mils)	4 cm (1.6 in)	22.5 cm (8.9 in)
	0.5 mm (20 mils)	6 cm (2.4 in)	67 cm (26.4 in)
	1 mm (40 mils)	14 cm (5.5 in)	117 cm (46.1 in)
EAN/UPC	0.33 mm (13 mils)	5 cm (2.0 in)	40 cm (15.8 in)
PDF417	0.25 mm (10 mils)	4 cm (1.6 in)	23 cm (9.1 in)
DataMatrix	0.38 mm (15 mils)	4 cm (1.6 in)	36 cm (14.2 in)
	0.25 mm (10 mils)	5 cm (2.0 in)	18 cm (7.1 in)

³ The reading distances for each scanner are typical distances measured from the front end of the scanner bezel in an office environment (200 lux) with extended reading range activated (if applicable).

North America

6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348 2600
Fax: (425) 355 9551

North Latin America

Mexico
Phone: (+52) 55 52 41 48 00
Toll Free NOLA:
01800 490 4990

South Latin America

Brazil
Phone: (+55) 11 3711 6770
Fax: (+55) 11 5502 6780

Europe, Middle East & Africa

Reading, United Kingdom
Phone: (+44) 118 923 0800
Fax: (+44) 118 923 0801

Asia Pacific

Singapore
Phone: (+65) 6303 2100
Fax: (+65) 6303 2199

Media Sales

EMEA: (+31) 24 372 3167
USA: (513) 874 5882
<http://intermec.custhelp.com>

Sales

Toll Free NA: (800) 934 3163
Toll in NA: (425) 348 2726
Freephone ROW:
00800 4488 8844

OEM Sales

Phone: (425) 348 2762

Customer Service & Support

Toll Free NA: (800) 755 5505
Toll in NA: (425) 356 1799
EMEA: intermec.custhelp.com

Internet

www.intermec.com

Worldwide Locations

www.intermec.com/locations

Intermec[®]
by Honeywell



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

