

Industrial Thermal Printer | CLe Series



GENERAL SPECIFICATIONS

CL408e-RFID | CL412e-RFID

PRINTER MODEL		CL408e-RFID	CL412e-RFID
PRINT SPECIFICATIONS			
Printing Method		Direct Thermal/Thermal Transfer	
Print Resolution		203 dpi (8 dots/mm)	305 dpi (12 dots/mm)
Printing Speed		6 ips (100mm/sec)	
Maximum Print Area		4.1" (104 mm) W x 49.2" (1249 mm) L	4.1" (104 mm) W x 32.8" (833 mm)
MEDIA SPECIFICATIONS			
Sensor Type		Adjustable transmissive sensor for gap, Reflective sensor for black mark, Automatic, programmable top of form, Label present sensor (opt. w/dispenser), Ribbon-out sensor	
Media Type		Roll-fed or fanfold, die-cut or continuous direct thermal (thermal transfer) labels, synthetics, and tag stock with or without black mark, gap or notch.	
Media Size	Width	0.87" - 5.1" (22 mm - 131 mm)	
	Length	Minimum 0.24" (6 mm)	
	Caliper	0.01" (0.25 mm)	
Roll Diameter		8.6" (218 mm)	
Wind		Face In	
Maximum Ribbon Size		4.4" (111 mm) W x 1475' (450 m) L - Face In	
FONT/BARCODE SYMBOLOGIES			
Fonts		Bitmap - 12 proportional, mono-spaced and outline fonts (Code table 858). Scalable Internal CG Triumvirate® and CG Times® fonts. Optional Downloaded TrueType® fonts, scalable from 8 to 72 points	
Barcode Symbolologies	Linear	UPC-A, UPC-E, EAN-8, EAN-13, Code 39, Code 93, Code 128, Codabar, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet™, GS1-128, GS1-DataBar™	
	2-D	PDF417, Micro PDF417, Truncated PDF417, Maxicode™, Data Matrix, QR Code, Composite Symbolology	
Formatting		360° rotation of barcodes and text, horizontal and vertical character expansion, sequential numbering, form overlay for high-speed editing of complex formats	
MEMORY			
Standard		16 MB RAM, 2 MB Flash	
Optional		4 MB Flash, 1 MB or 256 K PCMCIA	
Processor		32-BIT RISC	
RFID			
Formats		HF (High Frequency) Standards Supported: Tag-it™, I-Code, ISO 15693; UHF (Ultra-High Frequency) Standards Supported: EPC Class 1, ISO 18000-06B, EPC Class 0/0+, EPC Gen 2	
Features		Print-Write-Print for out of Spec Tags; RFID Counters; Calibration for New Inlay Types	
COMMUNICATION INTERFACE			
Plug-In Interface		Serial - RS232 (up to 57.6k bps), Parallel - IEEE1284 (ECP), Ethernet - 10/100BaseT, Wireless 802.11g, Twinax/Coax, RS422/485, USB	
SUPPORT			
Graphic		Printing and storage of *.PCX, *.BMP format, SATO Hex/binary	
Software		32 and 64-bit Windows® Drivers (Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008 and Windows 7) Label Software (Label Gallery Free), Printer Utilities	
OPERATING CHARACTERISTICS			
Electrical Requirements		115V/220V (± 10%), 50/60 Hz (± 1%) - Jumper switch required	
Environment	Operating	41° to 104°F (5° to 40°C), 15-85% RH, non-condensing	
	Storage	23° to 140°F (-5° to 60°C), Maximum 90% RH, non-condensing	
	EDS	8kV	
Agency Certifications		CE, UL, CSA, TÜV	
Dimensions		10.7" (271 mm) W x 16.9" (430 mm) D x 12.6" (321 mm) H	
Weight		28.7 lbs (13 kg)	
OPTIONAL ACCESSORIES			
Label Cutter, Label Dispenser, Label Rewinder, Memory Expansion, Real Time Clock, Plug-In Interface, Label Gallery			

SATO AMERICA, INC.

CORPORATE

10350-A Nations Ford Rd
Charlotte, NC 28273
Phone: (704) 644-1650
Fax: (704) 644-1662
satosales@satoamerica.com

LABEL MANUFACTURING, SERVICE & SALES

NORTH AMERICA	BRAZIL	ARGENTINA
Illinois	Sao Paulo	Buenos Aires
Florida		
New Jersey		
North Carolina		

©2013 SATO America, Inc. All rights Reserved. Rev F • Specifications subject to change without notice • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

