

# Affordable **Compact** Desktop Printers for Unrivalled Performance, Convenience & Versatility

Prints 4" Labels, Receipts, Wristbands and Tags



## CG4 Series

### INDUSTRY VERTICALS

- Healthcare
- Retail
- Transportation & Logistics
- Manufacturing
- Office

### APPLICATIONS

- Carton / Package Labelling
- Small Office Mailing
- Shelf-edge labelling
- Product Labelling
- Healthcare Specimen Labelling
- File Folder Labelling

### FEATURES

- Supports Input from Keypad
- 203 and 305dpi Print Resolution
- 4MB Flash Memory
- Thermal Transfer and Direct Thermal
- Anti-Microbial Casing
- Multiple Codepage Support
- Multiple Printer Language-Compatible Options
- Safety Top Cover Latch

### ACCESSORIES



#### Keypad

- Graphical LCD display
- Alphanumeric and one-touch function keys
- SD card supported
- Enables stand-alone printing (eliminates need to connect to a PC)



#### Dispenser

- Simplifies separation of labels from a backing paper for immediate label application



#### Cutter

- Precisely cut individual labels and tags
- Allows continuous printing and cutting of labels and tags

#### ▶ Standalone Capability Using Keypad

- SATO Keypad allows users to Format, Store, Input & Print without connecting to PC
- Label formats can be stored, and called on at time of printing

#### ▶ Flexible Use & Compatibility With Legacy Systems

- 2 Standard Communication Interface configurations: USB and RS232C; or USB and LAN; or USB and Parallel
- Parallel port allows printer to be connected to legacy systems

#### ▶ High Quality Printing

- Suitable for printing graphics and logos, 2D barcodes or patient's photo on wristbands

#### ▶ User-Friendly Operation & Maintenance

- Intuitive label mechanism design allows media loading in 3 simple steps: Drop-Load-Go
- User-friendly maintenance

The One-touch, tool-less print head release mechanism enables the print head to be quickly and easily replaced

Printer Platen Roller can be replaced without the need for any tools

#### ▶ Waste-Reducing

- Linerless kit option to print linerless labels, which come without liner or backing paper, therefore less paper waste

#### ▶ Print Labels with Date/Time Stamps Using Real-Time Clock Feature

#### ▶ Safe For Use

- Anti-microbial casing makes it suitable for applications in clean environments such as hospitals and in food preparation

#### ▶ Compatible

- Printer language options enables replacement of competitive printer models with minimal reprogramming of data streams

# General Specifications

CG4



PRINTER MODEL		CG408	CG412
PRINT SPECIFICATIONS			
Print Method		Direct Thermal/Thermal Transfer	
Print Resolution		8 dots/mm (203dpi)	12 dots/mm (305dpi)
Max Print Speed		100mm/sec (4ips)	
Max. Print Area		(WxP): 104 x 300mm (4.09" x 11.81")	
CPU		32 Bits RISC-CPU 64MHz	
Printer Body Memory		Main Memory (Flash ROM): 4MB byte, SDRAM: 8MB byte	
MEDIA SPECIFICATIONS			
Sensor Type		I-Mark Sensor (Reflection type), Label Gap Sensor (Transparent type)	
Media	Label Size	Continuous	L: 7 ~ 300mm (0.28" ~ 11.81"), With backing paper: 10 ~ 303mm (0.39" ~ 11.93") W: 22 ~ 107mm (0.87" ~ 4.21"), With backing paper: 25 ~ 110mm (0.98" ~ 4.33")
		Tear-Off	L: 22 ~ 300mm (0.87" ~ 11.81"), With backing paper: 25 ~ 303mm (0.98" ~ 11.93") W: 22 ~ 107mm (0.87" ~ 4.21"), With backing paper: 25 ~ 110mm (0.98" ~ 4.33")
		<b>Label without Adhesive</b>	
	Label Thickness	Continuous	L: 10 ~ 303mm (0.39" x 11.93"), W: 25 ~ 110mm (0.98" x 4.33")
		Tear-Off	L: 25 ~ 303mm (0.98 x 11.93"), W: 25 ~ 110mm (0.98" x 4.33")
	Wind Direction	Face-in/Face-out	
Media Roll Size	Max external diameter: 128mm (5.04"), Paper core inner diameter: 40mm (1.57")		
Ribbon Size	Length	Max 100m	
	Width	110mm +/- 0.5mm (4.33" +/- 0.002)	
	Wind Direction	Face Out	
FONT/SYMBOLOGIES			
Standard Fonts	Bitmap Fonts	Alphanumerical and Symbol: WB (18x30 dot), WL (28x52 dot), XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)	
	Rasterized Fonts	CG Times, CG Triumvirate, CG Times Bold, CG Triumvirate Bold	
Barcode	1D Barcode	UPC-A/ UPC-E, EAN8/13, CODE39, CODE93, CODE128, GS1-128 (UCC/EAN128), CODABAR(NW-7), ITF, INDUSTRIAL 2of5, MATRIX 2of5, BOOKLAND, MSI, POSTNET, GS1 DATABAR (RSS)	
	2D Barcode	PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)	
Composit Symbols		EAN-13 Composite (CC-A/CC-B), EAN-8 Composite (CC-A/CC-B), UPC-A Composite (CC-A/CC-B), UPC-E Composite (CC-A/CC-B), GS1-128 Composite (CC-A/CC-B/CC-C), GS1 DataBar Composite (CC-A/CC-B), GS1 DataBar Truncated Composite (CC-A/CC-B), GS1 DataBar Stacked Composite (CC-A/CC-B), GS1 DataBar Stacked Omni-Directional Composite (CC-A/CC-B), GS1 DataBar Limited Composite (CC-A/CC-B), GS1 DataBar Expanded Composite (CC-A/CC-B), GS1 DataBar Expanded Stacked Composite (CC-A/CC-B)	
Print Direction		Character & Barcode: 0°, 90°, 180°, 270°	
COMMUNICATION INTERFACE			
Interface		USB (B Type) + RS-232C (D-SUB 9 Pin) Model, USB (B Type) + LAN (10BASE-T/100BASE-TX Auto Switching) Model, USB (B Type) + IEEE1284 Model	
Command		SBPL	
OPERATING CHARACTERISTICS			
Power Requirements	AC Adaptor	Input Voltage: AC100V ~ 240V +/- 10%, Rated Input Voltage: AC100V / AC240V, Output Voltage: 19V	
Consumption Voltage		At Peak: 50W, At Waiting: 2.5W	
Environment	Operating	4 ~ 38°C / 30 ~ 80% RH (without condensing)	
	Storage	-10 ~ 60°C / 15 ~ 85% RH (without condensing)	
Dimension		(WxDxH): 179 x 238 x 173mm (7.05" x 9.37" x 6.81") Except protrusion part	
Weight		DT: 1.7kg (3.5 lbs) TT: 1.9kg (4.2 lbs)	
OPTIONS		Cutter, Dispenser, RTC, Linerless Kit (without cutter), Keypad, Unwinder, SATO Label Gallery™	
MISCELLANEOUS			
Regulatory Approvals		USA/CANADA: UL60950-1 (2001), CSA22.2 No. 60950-1-03, EUROPE: EN60950-1, CE CHINA: CCC (GB4943-2001)	
Antibacterial Finishing		Resin of the enclosure/control panel includes an antibacterial substance. This substance is tested according to JIS Z 2801. JIS stands for Japanese Industrial Standard; JIS Z 2801 was designed to quantitatively measure the ability of an antimicrobial surface to kill or inhibit the growth of microorganisms.	

## Contact For a full list of all SATO offices, please refer to [www.satoworldwide.com](http://www.satoworldwide.com)

### AMERICAS

#### SATO INTERNATIONAL AMERICA, INC.

(Regional Sales HQ)  
P: +1 704 644 1650  
E: [satosales@satoamerica.com](mailto:satosales@satoamerica.com)  
W: [www.satoamerica.com](http://www.satoamerica.com)

#### SATO AMERICA, INC.

P: +1 704 644 1650  
E: [satosales@satoamerica.com](mailto:satosales@satoamerica.com)  
W: [www.satoamerica.com](http://www.satoamerica.com)

#### SATO LABELING SOLUTIONS AMERICA, INC.

P: +1 630 771 4200  
E: [sales@satolabeling.com](mailto:sales@satolabeling.com)  
W: [www.satolabeling.com](http://www.satolabeling.com)

### EUROPE

#### SATO INTERNATIONAL EUROPE N.V.

(Regional Sales HQ)  
P: +32 (0)2 788 80 00  
E: [info@be.satoeurope.com](mailto:info@be.satoeurope.com)  
W: [www.satoeurope.com](http://www.satoeurope.com)

### SATO UK LTD.

P: +44 (0) 1255 2400 00  
E: [enquiries@satouk.com](mailto:enquiries@satouk.com)  
W: [www.satouk.com](http://www.satouk.com)

### SATO LABELLING SOLUTIONS EUROPE GmbH

P: +49 6272 9201 324  
E: [info@de.satoeurope.com](mailto:info@de.satoeurope.com)  
W: [www.satoeurope.com/de](http://www.satoeurope.com/de)

### SATO POLSKA SP. Z O.O.

P: +48 71 381 03 60  
E: [info@pl.satoeurope.com](mailto:info@pl.satoeurope.com)  
W: [www.satoeurope.com/pl](http://www.satoeurope.com/pl)

### SATO FRANCE S.A.S.

P: +33 (0)3 20 62 96 40  
E: [info@fr.satoeurope.com](mailto:info@fr.satoeurope.com)  
W: [www.satoeurope.com/fr](http://www.satoeurope.com/fr)

### SATO IBERIA S.A.U.

P: +34 902 333 341  
E: [info@es.satoeurope.com](mailto:info@es.satoeurope.com)  
W: [www.satoeurope.com/es](http://www.satoeurope.com/es)

### ASIA PACIFIC AND OCEANIA

#### SATO INTERNATIONAL ASIA

#### PACIFIC PTE. LTD.

#### (Regional Sales HQ)

P: +65 6271 5300  
E: [sales@satoasiapacific.com](mailto:sales@satoasiapacific.com)  
W: [www.satoasiapacific.com](http://www.satoasiapacific.com)

#### SATO ASIA PACIFIC PTE. LTD.

P: +65 6271 5300  
E: [sales@satoasiapacific.com](mailto:sales@satoasiapacific.com)  
W: [www.satoasiapacific.com](http://www.satoasiapacific.com)

#### SATO AUTO-ID MALAYSIA SDN. BHD.

P: +60 3 7620 8901  
E: [sales@satosms.com.my](mailto:sales@satosms.com.my)  
W: [www.satoasiapacific.com](http://www.satoasiapacific.com)

#### SATO AUTO-ID (THAILAND) CO., LTD.

P: +662 736 4460  
E: [sales@satothailand.co.th](mailto:sales@satothailand.co.th)  
W: [www.satoasiapacific.com](http://www.satoasiapacific.com)

### SATO SHANGHAI CO., LTD.

P: +86 (021) 6306 8899  
E: [sales@satochina.com](mailto:sales@satochina.com)  
W: [www.satochina.com](http://www.satochina.com)

### SATO AUSTRALIA PTY LTD.

P: +61 3 8814 5330  
E: [sales@satoaustralia.com](mailto:sales@satoaustralia.com)  
W: [www.satoaustralia.com](http://www.satoaustralia.com)

### SATO NEW ZEALAND LTD.

P: +64 9 477 2222  
E: [sales@satonewzealand.com](mailto:sales@satonewzealand.com)  
W: [www.satonewzealand.com](http://www.satonewzealand.com)



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

Get in touch with us  
on social media!

