





# XT3215

## **KEY FEATURES**

- Intel D525 / 1.8GHz dual core
- 2GB DDR3 memory (4GB maximum)
- Resistive Touch
- Fan Free
- Dual Gigabit LAN
- Digital Brightness Control
- VESA Mount Capability
- Slim, folding base design
- Optional Solid State Drive and WiFi

### **About Posiflex**

- Designer and manufacturer of Point-of-Service and industrial touch terminals
- Revolutionary technology, reliable quality, reasonable pricing and recognized service
- Delivers reliable terminals for maximum uptime and lower total cost of ownership
- Comprehensive suite of peripherals and services
- Innovative excellence since 1984 with more than 30 patents for innovation
- Global presence
- Two ISO 9001/9002/14001 Certified Facilities

## Flexible, Cost-Effective Workhorse

The XT3215 is designed for environments when cost and performance is a critical factor. Even though the XT3215 has exceptional price / performance, its quality has a foundation in the long legacy of Posiflex field-tested reliability.

The XT3215 base folds and configures to an optimal angle and space. The low-profile design fits in the tightest of spaces, reducing shipping costs up to 40%. With this sleekly designed fan-free exterior comes the Intel D525 1.8GHz dual core power to run many applications for hospitality, retail, health care and more.

The XT3215 features an Intel D525 1.8GHz dual core, 2GB standard DDR3 RAM (4 GB maximum) and a 15" resistive touch TFT LCD touch screen terminal. Along with a rich array of connectivity features are options for a mini-PCIe slot for WiFi and VESA wall mount bracket.

Specifications	XT3215
Processor	Intel D525 / 1.8GHz / 1M Smart Cache (dual core)
System Memory	DDR3 800MHz SO-DIMM x 1, max. 4GB, factory default 2GB
Storage Device	SATA Storage x 2, factory default 320GB HDD x 1
Supported OS	POSReady 2009 / POSReady 7 / Windows 7 / Linux per request
Touch	Resistive
Physical Dimensions	
Dimensions (WxDxH) in.	14.6" x 12.6" x 9.9"
Display	15" TFT LCD with 1024x768 resolution
Weight (lbs)	12.3

Weight (lbs)	12.3
Connectivity	
LAN Port	10 / 100 / 1000 Mb x 2
Serial Port	4, DB9 x 3 + RJ45 x 1, 5V / 12V support on all COM ports
VGA PORT	VGA x 1, 12V support for Posiflex monitors
Standard USB Port	5 (4 on I/O panel, 1 on side)
Mini-PCIe slot	Optional
CR PORT	1, control 2 CR via optional Y-cable

## **Options**

SSD

Parallel Port with optional extension cable

WB-5000 wall mount bracket

WiFi

Peripherals	
MSR w/ Optional Finger Print	SA100, SA300
Pole Display	PD2605, PD2608
Secondary Monitor	LM3010
Printer	PP9000
Cash Drawer	CR6300, CR3100

<sup>\*\*</sup> The product information and specifications are subject to change without prior notice.

SECONDARY DISPLAYS	MAGNETIC STRIPE READERS	CASH DRAWERS	RECEIPT PRINTER
PD2608 PD2605 LM3010 Bezel-Free Rear Mount (not pictured)	SA100 SA300 Optional: Fingerprint Reader	CR3100 Adjustable Coin Slot  CR6300 Fixed Coin Slot	PP9000

### **Available Services**

- **Standard and Extended Warranty** Extend your depot warranty up to 5 years.
- **Advance Exchange** We ship overnight replacement equipment directly to your business. You return the faulty unit to Posiflex.
- OnSite Service Expert technicians will efficiently handle the complete equipment swap and return process.
- Regional Repair Depots Three regional depots assure fast turn-around time on repairs.
- Post Warranty Support Spare parts, in addition to a flat rate repair program, for post warranty needs.
- Installation Services Let our nationwide network of experts stage and install your equipment.
- OEM Design and Integration **Our Product Development** Team helps design equipment, for custom hardware applications.





















Posiflex designs, engineers and manufactures:



www.L-TronDirect.com 800-830-9523 info@L-Tron.com

