

ZD420 4-Inch Thermal Transfer Printer UNIQUE AND INTELLIGENT TIME-SAVING RIBBON CARTRIDGE FOR FOOL-PROOF INSTANT LOADING

If you need a fast 4-inch printer that is easy to use, easy to deploy and easy to manage, choose the leader of the class — the ZD420. A new ribbon cartridge and more status icons maximize uptime by making using the printer easier than ever to use. With virtually every modern wired and wireless connectivity option and support for many printer languages, deployment is always fast and easy — just unplug your existing printer, plug in the ZD420 and you're back up and running. Add new connectivity and media handling options whenever you need them, right on site. Monitor and manage all your ZD420 printers from the cloud, for unsurpassed management simplicity. And our optional Zebra OneCare service will help you maximize the availability and productivity of your ZD420 printers with unmatched from-the-manufacturer support that covers everything — from worn out printheads to normal wear and tear. The ZD420 — when ease of use, flexibility and management simplicity matter.



Groundbreaking ease of use

The ZD420 is loaded with features that make it the easiest printer to use in its class. The ZD420 is the only thermal printer to offer a ribbon cartridge, which takes just a few seconds to load, with fool-proof installation — the ribbon cartridge can only be loaded one way for first-time every-time instant loading. The crypto chip in the ribbon lets you know when the ribbon needs replacing. And with five intuitive status icons — status, pause, data, supplies and network — your workers can see at a glance what is needed to keep your Zebra printer up, running and available.

Get all the features you need today and easily add the features you need tomorrow

The movable media sensor gives you more media options, including media with off-center black marks, die-cut notches or multiple labels across the width.

With virtually every modern connectivity option, the ZD420 fits into your technology environment now and in the future. Choose from USB, auto-sensing serial or 10/100 Ethernet, as

well as the very latest wireless options: Wi-Fi certified 802.11ac WLAN and Bluetooth 4.1. And you can support wired and wireless users simultaneously.

If you need new communication or media handling options in the future, no problem. Add serial or Ethernet connectivity, plus a peeler or a cutter, right on site — without taking the ZD420 out of service. The result? Maximum functionality and uptime.

The ZD420 offers backwards compatibility with existing applications and formats, plus support for Zebra ZPL and EPL printer languages and many non-Zebra languages, making it easy to upgrade your aging Zebra or competitive printers — just plug in the ZD420 and you're back up and running.

Easy to clean and sanitize healthcare model

The ZD420 is available in a healthcare model with disinfectant-ready plastics and a sealed button interface that makes it easy to clean and disinfect— crucial in hospitals and clinics. The ZD420 fits easily in space constrained pharmacies, labs and nurses stations. And with its 300 dpi printing option, even the small labels on specimen containers and prescriptions are highly legible.

Link-OS for unparalleled ease of management

The ZD420 supports Zebra's Link-OS, a unique software platform that makes it easier than ever to integrate, manage and maintain your printers, from any location. With this innovative highly flexible solution, you can manage one printer, a group of specific printers or all printers anywhere in the world via the cloud. And with a quick tap of an NFCenabled mobile device on the ZD420, you can access Zebra's extensive knowledge base of how-to videos and more, making it easy to obtain the information needed to quickly resolve everyday printer issues.



THE ZD420 - WHEN EASE OF USE, FLEXIBILITY AND MANAGEMENT SIMPLICITY MATTER.

FOR MORE INFORMATION, VISIT WWW.ZEBRA.COM/ZD420 OR OUR GLOBAL CONTACT DIRECTORY AT WWW.ZEBRA.COM/CONTACT

ZD420 Specifications Chart

STANDARD FEATURES **OPTIONS AND ACCESSORIES** Thermal Transfer print method Field installable dispenser - label peel and Media Handling ZPL and EPL programming languages present with label present sensor; field installable cutter 5 status icon, 3 button user interface USB 2.0, USB Host Field installable RS-232 auto-sensing Serial, Communications Bluetooth low energy DB-9; Ethernet - 10/100 internal; factory OpenACCESS[™] for easy media loading installed wireless dual radio: 802.11ac Wi-Fi Dual-wall frame construction and Bluetooth 4.1 ENERGY STAR qualified Real Time Clock Healthcare Healthcare model with IEC 60601-1 Model compliant power supply and healthcare PHYSICAL CHARACTERISTICS wipeable plastics Dimensions 10.0 in. L x 8.0 in. W x 7.0 in. H Keyboard ZKDU keyboard display units for stand-alone 254 mm L x 202 mm W x 177 mm H **Display Unit** printing solutions 5.0 lbs./2.3 kg Weight FONTS/GRAPHICS/SYMBOLOGIES PRINTER SPECIFICATIONS **Bar Code Ratios** 2:1 and 3:1 Resolution* 203 dpi/8 dots per mm Optional 300 dpi/12 dots per mm 1D Bar Codes Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC Resolution can be factory installed or and EAN 2-or 5-digit extensions, Plessey, changed on site via accessory kits. Resolution can be changed from 300 dpi to Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar 203 dpi, as well as from 203 dpi to 300 dpi. and Planet Code Memory 512 MB Flash; 256 MB SDRAM Codablock, PDF417, Code 49, DataMatrix, 2D Bar Codes 4.09 in./104 mm for 203 dpi and 300 dpi Maximum MaxiCode, QR Code, MicroPDF, Aztec Print Width Fonts and 16 resident expandable ZPL II bitmap fonts 6 in./152 mm per second (203 dpi) Maximum Graphics Two resident scalable ZPL fonts 4 in./102 mm per second (300 dpi) Print Speed Five resident expandable EPL2 fonts Media Sensors Full width, moveable reflective/black mark Native open-type font support sensor: multi-position transmissive/ Unicode compliant for multi-language, on gap sensor demand thermal printing China units include SimSun simplified ZPL II; EPL 2; XML; ZBI Firmware Chinese font 64 MB user available non-volatile memory, MEDIA CHARACTERISTICS 8 MB user available SDRAM Maximum 39.0 in./991 mm **PRINTER SUPPLIES** Label Length Maximum Label 4.65 in./118 mm Keep your Zebra printer up and running with genuine Zebra and Media Width printer supplies, available directly from Zebra Media Roll Size 5.00 in./127 mm outer diameter Core inner REGULATORY diameter: 0.5 in. (12.7 mm) and 1.0 in. (25.4 mm) IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, standard, 1.5 in. (38.1), 2.0 in., (50.8 mm) and EN61000-3-3, FCC Class B, ICES-003, FCC 15, 209; 15, 247(d), 3.0 in. (76.2 mm) using optional adapters IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus Thickness 0.003" (0.08mm) min.; 0.0075 (.1905mm) max. CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, (tear-off mode only) SABS, IN-Metro, BIS, NOM Media Types Roll-fed or fan-fold, die cut or continuous SOFTWARE TOOLS with or without black mark, tag stock. continuous receipt paper, and wristbands Link-OS: Document Design: Quickly design a customized **OPERATING CHARACTERISTICS** print solution using your business data and Zebra's intuitive, plug-and-print design tools. Operating Temp. 40° to 105° F/4.4° to 41° C Device Integration: Zebra offers apps and products designed to help you integrate Zebra devices into your existing systems. -40° to 140° F/-40° to 60° C Storage Temp. Device Management: Manage your print operations locally 10% to 90% non-condensing Operating and globally with Zebra's suite of device management tools. Humidity Developer Tools: Provides you the tools you need to create Storage Humidity 5% to 95% non-condensing your own apps, including documentation, source code, programming languages, templates and more Electrical Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz; ENERGY STAR qualified **RECOMMENDED SERVICES**

Zebra OneCare Select



NA and Corporate Headquarters +1 800 423 0442 inquiry4@zebra.com Asia-Pacific Headquarters +65 6858 0722 contact.apac@zebra.com EMEA Headquarters zebra.com/locations mseurope@zebra.com Latin America Headquarters +1847 955 2283 la.contactme@zebra.com

©2016 ZIH Corp and/or its affiliates. All rights reserved. Zebra and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. Part number: SS-ZD420 2/2016

The ZD420 is ideal in:

Light Manufacturing

- Agency labels/ nameplates
- Product labels
- Apparel tags

Transportation & Logistics

Asset labels

Healthcare

- Lab and specimen labels
- Asset labels
- Blood and IV bag labels
- Sterile services

Retail

- Asset labels
- Shelf labels
- Record labels

Government

- Asset labels
- Record labels

Services

 Service reminder labels



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

Get in touch with us on social media!

www.L-Tron.com