



# Zebra® ZT200™ Series



SEE MORE. DO MORE.



Zebra's most affordable industrial printers, the ZT200 Series, incorporate extensive customer feedback and the learnings from legacy printers—creating innovative printers with a space-saving design. Featuring Zebra's Link-OS® environment, the ZT200 Series provides users with effortless setup, intuitive operation and ease of service and maintenance.

Whether you are adopting barcode technology for the first time or upgrading existing printer models, the ZT200 Series is the right choice for a variety of labeling applications. These innovative printers provide many user benefits.

The ZT200 Series offers a streamlined design and smaller footprint that takes up less physical space than the Stripe and S4M models. ZT200 Series printers require minimal operator training and benefit from tool-less standard component maintenance and a durable design to minimize service.

Your IT staff will appreciate the backwards compatibility, since it allows for new printers to be up and running with minimal time and effort.

The ZT200 Series has been designed for ease of use, versatility and outstanding value.

## Ideal for These Applications

**Manufacturing:** work-in-process, product ID/serial numbers, packaging labels, receiving/put-away labeling

**Transportation & Logistics:** order picking/packing, shipping/receiving, cross-docking, compliance labeling

**Healthcare:** orders, specimen labels, asset-tracking, unit-of-use labeling

**Retail:** shelf-labeling, shipping, returns, item tags

**Government:** asset-tracking, logistics labeling, warehousing

# YOU SPOKE. WE LISTENED.

## ZT200 SERIES PRINTER BENEFITS— DESIGNED WITH YOU IN MIND.

---

The ZT200 Series design is the culmination of extensive feedback from our customers and understanding their printing applications, evolving business needs and operational challenges. The ZT200 Series offers outstanding functionality and features at an exceptional value.

### Space-Saving Design

---

- Compact footprint and streamlined design fits easily in confined areas where space is at a premium
- Space saving design with unique bi-fold door (requires 4 in./102 mm of opening space) fits easily into tight spaces maximizing work space

### Fast Installation and Integration

---

- Ideal replacement printer for previous generation Stripe and S4M models
- Multiple connectivity options: Parallel, 10/100 Ethernet, 802.11a/b/g/n wireless
- Icon-based status LEDs provide immediate and easily visible printer status
- Virtual Devices apps enable Link-OS printers to support well-known legacy and competitor printer languages—in addition to ZPL<sup>®</sup> and EPL<sup>™</sup>—for a future-proofed investment

### Intuitive, Effortless Media Loading

---

- Side-loading design eliminates complicated threading of supplies
- Color-coded cues give even first-time users visual guidance for loading ribbon and media
- Illuminated multi-position transmissive and reflective sensors are visible through the media for trouble-free sensor-position adjustment

### Print Quality

---

- Engineered for greater print precision with fine-tuned adjustments
- Crisp, clean text and barcodes—even on narrow media

### Zebra Reliability and Durability

---

- Built for light industrial and commercial environments
- ENERGY STAR<sup>®</sup> qualified printer
- Drive system designed for optimal performance, with minimal maintenance required

### Simplified Serviceability

---

- Easy, tool-less platen and printhead removal enable simple cleaning and replacement
- Simple interchangeable connectivity options enable rapid printer changes and upgrade
- Only three common tools needed for basic service

### The Link-OS Environment In-depth

---

To meet changing expectations and growing demands for devices that are mobile, intelligent and connected to the Cloud, Zebra created a new software platform to support its devices: Zebra's Link-OS environment. This innovative solution makes Zebra printers even easier to integrate, manage and maintain than ever before—from any location.

The Link-OS environment is highly flexible, allowing new and creative ways for users to develop applications that interact with Zebra printers from mobile devices located anywhere in the world. Users can perform updates, gather data, and make smarter business choices from new analytic-driven insights.

**Link-OS<sup>®</sup>**

# COMPARING THE ZT220™ AND THE ZT230™



The ZT200 Series offers two models—the ZT220 and the ZT230. Compare the features to see which printer best suits your needs.

|  <p><b>ZT230</b></p>  |  <p><b>ZT220</b></p>   |
|--|---|
| <ul style="list-style-type: none"> <li>• S4M replacement that easily integrates into your environment</li> </ul>   | <ul style="list-style-type: none"> <li>• Zebra’s most affordable industrial printer</li> </ul>  |
| <ul style="list-style-type: none"> <li>• Rugged all-metal case for long-lasting use</li> </ul>   | <ul style="list-style-type: none"> <li>• Durable high-impact polymer case for long-lasting use</li> </ul>   |
| <ul style="list-style-type: none"> <li>• 450 m/1476’ ribbon capacity for increased uptime and fewer ribbon changes</li> </ul>  | <ul style="list-style-type: none"> <li>• 300 m/984’ ribbon capacity</li> </ul>  |
| <ul style="list-style-type: none"> <li>• Graphical LCD user interface for easy printer setup and control</li> </ul>  | <ul style="list-style-type: none"> <li>• Simple single-use three-button user interface</li> </ul>   |
| <ul style="list-style-type: none"> <li>• Ideally suited for barcode labeling applications requiring more frequent format or printer setting changes through use of the intuitive user interface</li> </ul> | <ul style="list-style-type: none"> <li>• Ideally suited for barcode labeling applications where minimal format or printer setting changes are required</li> </ul> |

**ZebraCare™ Services**

Increase printer uptime and reduce lost productivity and unbudgeted repair costs by selecting a ZebraCare service agreement. A cost-effective means of planning and budgeting for your annual maintenance expenditures, your agreement ensures that trained Zebra technicians will bring your printer back to factory specifications. Zebra offers a variety of plans to fit your budget and business needs.

**Genuine Zebra™ Supplies**

Zebra’s comprehensive range of specialty supplies consists of self-adhesive labels, ribbons, card supplies, batteries and software for label design and printer network management. The Supplies R&D team carefully selects materials by conducting extensive tests to ensure consistent, high-quality cards, paper, labels and ribbon. We manufacture each supplies product using the same material every time to ensure crisp, readable and scannable output.

# SPECIFICATIONS AT A GLANCE\*

## Printer Name

ZT210 (not available in all Regions)  
ZT220  
ZT230

## Standard Features

- Print methods: direct-thermal or thermal-transfer (optional)
- Construction: metal frame with choice of metal (ZT230) or plastic (ZT220) media cover
- Bi-fold media door with large clear window
- Side-loading supplies path for simplified media and ribbon loading
- Element Energy Equalizer™ (E3™) for superior print quality
- Bi-color LEDs for quick printer status
- Icon-based LCD multilingual graphical user interface and full function keypad (ZT230)
- Simple keypad (ZT220)
- USB 2.0 and RS-232 Serial ports
- ENERGY STAR qualified

## Printer Specifications

### Resolution

- 203 dpi/8 dots per mm
- 300 dpi/12 dots per mm (optional)

### Memory

- 128 MB SDRAM memory
- 128 MB on-board linear Flash memory

### Maximum Print Width

4.09"/104 mm

### Maximum Print Speed

6"/152 mm per second

### Media Sensors

Transmissive and reflective sensors

### Media Characteristics

- Maximum label and liner width: 4.5"/114 mm
- Maximum non-continuous label length: 39"/991 mm

### Media Width

0.75"/19.4 mm to 4.50"/114 mm

### Print Length

- 203dpi: 157"/3,988 mm
- 300dpi: 73"/1,854 mm

### Maximum Media Roll Size

- 8.0"/203 mm O.D. on a 3.0"/76 mm I.D. core
- 6.0"/152 mm O.D. on a 1.0"/25 mm I.D. core

### Media Thickness

0.003"/0.076 mm to 0.010"/0.25 mm

### Media Types

Continuous, die-cut, notch, black mark

## Ribbon characteristics

(Thermal-transfer option only)

### Outside diameter

3.2"/81.3 mm on a 1.0"/25 mm I.D. core (ZT230)

### Standard length

300 m/984' (ZT220) or 450 m/1,476' (ZT230)

### Ratio

- 2:1 media-roll-to-ribbon ratio for ZT220
- 3:1 media-roll-to-ribbon ratio for ZT230

### Width

1.57"/40 mm to 4.33"/110 mm

### Ribbon Setup

Ribbon wound ink-side out, core to core

## Operating Characteristics

### Environmental

- Operating Temperature: 40° F/5° C to 105° F/40° C (Thermal Transfer) 32° F/0° C to 105° F/40° C (Direct Thermal)
- Storage/Transport Environment: -40° F/-40° C to 140° F/60° C
- Operating humidity: 20% to 85% non-condensing
- Storage humidity: 5% to 85% non-condensing

### Electrical

- Universal auto-ranging (PFC-compliant) power supply 100-240 VAC; 47-63 Hz
- ENERGY STAR qualified

### Agency Approvals

- IEC 60950, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3
- **ZT210:** CCC
- **ZT220:** cTUVus, CE, FCC, ICES-003, VCCI, C-Tick, NOM, Gost-R, BSMI, S-Mark (Argentina), KC, CCC, UkrSepro, SIL, SABS
- **ZT230:** cTUVus, CE, FCC, ICES-003, VCCI, C-Tick, NOM, Gost-R, BSMI, S-Mark (Argentina), KC, CCC, UkrSepro, SIL, SABS

## Physical Characteristics

|         | ZT220 closed  | ZT230 closed  |
|---------|---------------|---------------|
| Width:  | 9.4"/239 mm   | 9.5"/242 mm   |
| Height: | 11"/280 mm    | 10.9"/277 mm  |
| Depth:  | 17"/432 mm    | 17"/432 mm    |
| Weight: | 17 lbs/7.8 kg | 20 lbs/9.1 kg |

## Options and Accessories

### Media Handling

- Peel – a front-mount, passive-peel with no take-up spindle
- Peel – a front-mount, passive-peel with liner take-up spindle (factory-fit only)
- Cutter – a front-mount guillotine cutter

### Real Time Clock (RTC)

- Real Time Clock
- Date/time for standalone applications

### Keyboard Display Unit

Supports KDU Plus™ and ZKDU: Enter variable data and retrieve stored forms for standalone applications

## Communication

- ZebraNet® a/b/g/n Print Server (internal)
- ZebraNet® 10/100 Print Server (internal or external)
- Centronics® Parallel port (internal)

## Link-OS Solutions

### Software Tools

- **Document Design:** Quickly design a customized print solution using your business data and Zebra's intuitive, plug-and-print design tools.
- **Device Integration:** Zebra offers apps and products designed to help you integrate Zebra devices into your existing systems.
- **Device Management:** Manage your print operations locally and globally with Zebra's suite of device management tools.
- **Developer Tools:** Provides you the tools you need to create your own apps, including documentation, source code, programming languages, templates and more.

## Firmware

- ZPL II®
- Zebra Global Printing Solution
- EPL™†
- Web View & Alert
- ZBI 2.0 (optional)

## Barcode Symbolologies

- **Linear barcodes:** Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN with 2 or 5 digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, Planet Code
- **2-Dimensional:** Aztec, Codablock, PDF417, Code 49, Data Matrix, MaxiCode, QR Code, MicroPDF417, TLC 39, RSS-14 (and composite)

## Fonts and Graphics

- 7 bitmapped, 1 smooth-scalable (CG Triumvirate™ Bold Condensed). Contains UFST® from Agfa Monotype
- Pre-loaded Unicode™-compliant scalable fonts for EMEA character sets
- International character sets supporting the following code page: IBM® Code Page 850
- Supports user-defined fonts and graphics, including custom logos
- ZPL II drawing commands including boxes and lines
- 58 MB user available non-volatile memory storage for downloadable objects
- 4 MB user-available SDRAM

For optimum print quality and printer performance, use genuine Zebra supplies.



**Corporate Headquarters**  
+1 800 423 0442  
inquiry4@zebra.com

**Asia-Pacific Headquarters**  
+65 6858 0722  
apacchannelmarketing@zebra.com

**EMEA Headquarters**  
+44 (0)1628 556000  
mseurope@zebra.com

**Latin America Headquarters**  
+1 847 955 2283  
inquiry4@zebra.com

**Other Locations / USA:** California, Georgia, Illinois, Rhode Island, Texas, Wisconsin **Europe:** France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey, United Kingdom **Asia Pacific:** Australia, China, Hong Kong, India, Indonesia, Japan, Malaysia, Philippines, Singapore, South Korea, Taiwan, Thailand, Vietnam **Latin America:** Argentina, Brazil, Colombia, Florida (LA Headquarters in USA), Mexico **Africa/Middle East:** Dubai, South Africa

\*Specifications subject to change without notice. †EPL available on 203 dpi models only.

©2015 ZIH Corp. Zebra, representation of Zebra Head, ZebraNet, ZPL II, Element Energy Equalizer, E3, ZBI 2.0, ZBI-Developer, ZebraDesigner, and all product names and numbers are Zebra trademarks, and may be registered trademarks of ZIH Corp in certain jurisdictions. All rights reserved. ENERGY STAR and the ENERGY STAR mark are registered marks owned by the U.S. government. CG Triumvirate and UFST are trademarks of Monotype Imaging, Inc. and may be registered in certain jurisdictions. Unicode is a trademark of Unicode, Inc. IBM is a registered trademark of International Business Machines Corporation in the United States, other countries, or both. Centronics is a registered trademark of Centronics Data Computer Corporation. All other trademarks are the property of their respective owners.



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

Get in touch with us  
on social media!

